# ANSIZE

## **PERPENDICULARITY TESTERS**



 Optional accessory: dial test indicators, cylinder square (part no. 4710, for calibration), granite square (part no. 4141, for calibration) 1.378"

| 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.378" | 1.

Part No.	Range (H)	Perpendicularity (α)	Side perpendicularity (β)	L
4770-300E	0-12"	118µin	394µin	18.110"
4770-600E	0-24"	197µin	787µin	29.921"

### **CYLINDER SQUARES**




10

- Made of special alloy steel, hardness HRC58~60
- The handle can be removed

Part No.	Length (L)	Squareness
4710-200*	8"	39µin
4710-300*	12"	59µin

<sup>\*</sup>Supplied with manufacturer inspection certificate








4770-300E

### **GRANITE SQUARES**

CUSTOM-MADE SUPPLY SPECIAL SIZES ACCORDING TO CUSTOMER'S REQUEST

Part No.	Size (HxW)	Flatness of A	Flatness of B	Squareness of A to B	D
4141-250	9.8x6.3"	39µin	39µin	79µin	. 984"
4141-400	15.7x9.8"	59µin	39µin	118µin	1.575"
4141-630	24.8x15.7"	79µin	59µin	157µin	2.480"





# **GRANITE SQUARE**

CUSTOM-MADE SUPPLY SPECIAL SIZES ACCORDING TO CUSTOMER'S REQUEST

Part No.	Size (HxW)	Flatness of A, B, C and D	Squareness and parallelism between A, B, C and D
4144-315	12.4x12.4"	43µin	102µin



